



PVC Airtight 850gsm

PRODUCT: ATH112323

FEATURES:

- High airtightness and excellent stability
- Abrasion resistant
- Good colour fastness

APPLICATIONS:

- Inflatable kayaks, rafts, racing boats, rescuing equipment etc

SPECIFICATIONS:

Composition	1100Dtex*1100Dtex	DIN EN ISO 2060
	1000D*1000Denier	DIN EN ISO 2060
Weight	850gsm +/- 20gsm	DIN EN ISO 2286-2
Thickness	.70mm	DIN EN ISO 2286-2
Surface Finish	Matt	
Colour	Light Grey, Army Green, Various	
Breaking strength (warp x weft)	2900 x 2500 N/5cm	DIN 53354
Tearing strength (warp x weft)	370 x 350 N	DIN 53363
Adhesion strength	120 N/5cm	DIN 53357
Width	155cm	
Temperature resistance	-30°C ~70°C	DIN EN1876-2
Seam Strength	250 N/5cm	FTMS #5970
Weft Distortion	≤1.3 %	ASTM D3882
Flex Cracking (100000 times)	No Crack	DIN 53359
Recommend Pressure	6 Psi	

NOTE: All the above information shall only be used as a guide, customers shall independently test and determine the products stability. The mentioned data are average of test results as performed by the manufacturer.